

**MATERIAL SAFETY DATA SHEET**

This MSDS complies with 29 CFR 1910.1200

**SECTION 1 - PRODUCT IDENTIFICATION**

**PRODUCT** PAN based carbon fabric styles  
**FINISH** 470 (cleaned)  
**DESCRIPTION** Woven textile fabric

**SECTION 2 - HAZARDOUS INGREDIENTS**

CHEMICAL OR COMMON NAME	MAX. % BY WEIGHT	UN#	CAS#	TLV (SOURCE)	PEL (SOURCE)
Carbon fiber (textile grade)	100	not assigned	7440-44-0	not listed	not listed
Respirable fibrous carbon dust	not known*	not assigned	not assigned	5mg/m <sup>3</sup> (ACGIH) (inhalable)	5 mg/m <sup>3</sup> (OSHA) (respirable)

\*AMOUNT WILL BE DEPENDENT UPON METHOD OF HANDLING

**SECTION 3 - OTHER INGREDIENTS**

ITEMS LISTED IN THIS SECTION ARE EITHER CHEMICALLY OR PHYSICALLY BONDED TO THE FIBROUS GLASS TEXTILE AND ARE DEEMED NON-HAZARDOUS IN THE STATE SUPPLIED.

CHEMICAL AND COMMON NAME	MAX. % BY WEIGHT
Carbonous residual	0.5

**SECTION 4 - PHYSICAL DATA**

**Specific Gravity:** Approx. 2.0  
**APPEARANCE/PHYSICAL STATE:** Black; solid

**SOLUBILITY IN WATER:** Negligible

**ODOR:** No distinctive odor

**SECTION 5 - FIRE HAZARD DATA****FLASH POINT:** Not applicable**FLAMMABLE LIMITS:** Not applicable**EXTINGUISHING MEDIA:** Water, dry powder, or foam (needed for packaging only).**SPECIAL FIRE FIGHTING PROCEDURE:** In any sustained fire, wear self-contained breathing apparatus.**UNUSUAL FIRE HAZARDS:** In a sustained fire, combustible decomposition products may be released. These products include carbon dioxide, carbon monoxide, and airborne fibers. \*\***SECTION 6 - REACTIVITY DATA****STABILITY:** Stable**CONDITIONS/MATERIALS TO AVOID:** Note: Carbon fibers, dust, and fibrous particles are electrically conductive and can cause shorting in electrical equipment. Explosive shorting of high voltage systems is possible.**HAZARDOUS DECOMPOSITION PRODUCTS:** None generated under normal storage or handling conditions.**SECTION 7 - HEALTH HAZARD DATA****POTENTIAL ROUTES OF ENTRY:** Inhalation, skin contact**EFFECTS OF OVEREXPOSURE:** Direct skin contact with fibrous glass or its dust may cause mechanical irritation and transitory dermatitis. Breathing of fibers or dust may cause mechanical irritation of the mouth, nose, and throat.**EMERGENCY AND FIRST AID PROCEDURE:**

Inhalation: Move to fresh air area.

Ingestion: Not likely to occur through normal use, should ingestion occur seek medical attention.

Eyes: Flush with flowing water for 15 minutes - seek medical attention

Skin: Flush with ample cool water followed by washing with mild soap to remove accumulated fibers.

**CARCINOGEN:** Not classified as regulated under ACGIH, IARC, NTP, or OSHA. Industry studies have shown textile grade fibrous glass to be a non-carcinogen.**SECTION 8 - SPECIAL PROTECTION REQUIRED**

Exposure to fibrous glass may cause mechanical irritation to the skin, eyes, nose and throat. Typically such irritation occurs to newly exposed individuals, and usually diminishes after several days of exposure.

**RESPIRATORY:** If airborne dust or fibers exceed the TLV or if upper respiratory irritation occurs, use a respirator designed for nuisance type dusts.**VENTILATION:** Normal area ventilation is sufficient in most cases to keep dust and fiber levels below the TLV or PEL.**SKIN:** Barrier creams, gloves, and long sleeve loose fitting clothing may be required for certain workers who have sensitive skin or contact dermatitis. Work clothing should be laundered separately from other clothing before reuse.**EYE:** None required for normal use, but suggested as a good safety practice whenever use of the product releases fibrous carbon.**OTHER:** Observe good personal hygiene.

**SECTION 9 - CONTAINMENT AND DISPOSAL**

**CONTAINMENT AND CLEAN UP:** Dust or loose fibers can be vacuumed or swept with the aid of a dust suppressant.

**DISPOSAL:** Do not incinerate. Waste material should be bagged or containerized, sealed and dispose according to local, state, and federal laws. This material is not regulated under RCRA hazardous waste regulations.

**SECTION 10 - SPECIAL PRECAUTIONS**

**SHIPPING:** Not regulated by DOT; not classified by TDG

**STORAGE:** Store in dry area.

**HANDLING:** Carbon fibers, dust and fibrous particles are electrically conductive and can cause shorting in electrical equipment. Explosive shorting of high voltage systems is possible.

**SECTION 11 - REGULATORY INFORMATION**

**EPA, RCRA 40 CFR, Part 261, 1990:** Non-hazardous

**CERCLA:** Not listed

**SARA TITLE III:** Exempt by definition

**PA RIGHT-TO-KNOW:** Less than reportable quantity

**TSCA INVENTORY:** Exempt per section 8(a), 710.2(f), and 704.5(a)

**CA PROPOSITION 65:** Insignificant trace quantity

**MA RIGHT-TO-KNOW:** Less than reportable quantity

**NJ RIGHT-TO-KNOW:** Less than reportable quantity

**Revision Date:** February 23, 2011

**Technical/Emergency Information:** (336) 545-0011

**Prepared By:** Jacen Busick

**Title:** Chemist